

Compare the two following extracts.

**Extract 1**

(From a Garmin *Quick Start Manual*)



**Looking at Your nüvi**

1 See the *Important Safety and Product Information* guide in the product box for product warnings and other important information.

Power button:  
Press to turn the nüvi on and off.

Speaker Mini-USB connector  
microSD card slot  
Microphone

**Using the Main Menu**

- 1 GPS satellite strength.
- 2 Bluetooth® technology status.
- 3 Touch to select a usage mode.
- 4 Current time. Touch to change time settings.
- 5 Battery status.
- 6 Touch to find a destination.
- 7 Touch to view the map.
- 8 Touch to make a call when connected to a compatible mobile phone.
- 9 Touch to adjust the volume.
- 10 Touch to use the tools such as settings and Help.

*nüvi 1300 Series Quick Start Manual*

**Setting Up Your nüvi**

Before mounting the nüvi, see the *Important Safety and Product Information* guide for information about laws pertaining to windshield mounting.

**Mounting Your nüvi**

1. Remove the clear plastic from the suction cup. Place the suction cup on the windshield.
2. Flip the lever back toward the windshield.
3. Snap the cradle onto the suction cup arm.
4. Plug the vehicle power cable into the back of your nüvi.
5. Plug the other end of the vehicle power cable into a power outlet in your vehicle. Your unit should turn on automatically if it is plugged in and the vehicle is running. Follow the on-screen instructions.
6. Fit the bottom of your nüvi into the cradle.
7. Tilt your nüvi back until it snaps into place.
8. If you are using a traffic receiver in Europe, connect the external antenna to the traffic receiver and secure it to the windshield using the suction cups. (Traffic receivers are included in some nüvi packages.)

**WARNING:** This product contains a lithium-ion battery. To prevent damage, remove the unit from the vehicle when exiting or store it out of direct sunlight.

*nüvi 1300 Series Quick Start Manual*

**Looking at Your nüvi**

1 See the *Important Safety and Product Information* guide in the product box for product warnings and other important information.

Power button:  
Press to turn the nüvi on and off.

Speaker Mini-USB connector  
microSD card slot  
Microphone

**Using the Main Menu**

- 1 GPS satellite strength.
- 2 Bluetooth® technology status.
- 3 Touch to select a usage mode.
- 4 Current time. Touch to change time settings.
- 5 Battery status.
- 6 Touch to find a destination.
- 7 Touch to view the map.
- 8 Touch to make a call when connected to a compatible mobile phone.
- 9 Touch to adjust the volume.
- 10 Touch to use the tools such as settings and Help.

*nüvi 1300 Series Quick Start Manual*

**Setting Up Your nüvi**

Before mounting the nüvi, see the *Important Safety and Product Information* guide for information about laws pertaining to windshield mounting.

**Mounting Your nüvi**

1. Remove the clear plastic from the suction cup. Place the suction cup on the windshield.
2. Flip the lever back toward the windshield.
3. Snap the cradle onto the suction cup arm.
4. Plug the vehicle power cable into the back of your nüvi.
5. Plug the other end of the vehicle power cable into a power outlet in your vehicle. Your unit should turn on automatically if it is plugged in and the vehicle is running. Follow the on-screen instructions.
6. Fit the bottom of your nüvi into the cradle.
7. Tilt your nüvi back until it snaps into place.
8. If you are using a traffic receiver in Europe, connect the external antenna to the traffic receiver and secure it to the windshield using the suction cups. (Traffic receivers are included in some nüvi packages.)

**WARNING:** This product contains a lithium-ion battery. To prevent damage, remove the unit from the vehicle when exiting or store it out of direct sunlight.

*nüvi 1300 Series Quick Start Manual*

**Extract 2: Taken from the following reference:**

Truss, L. 2003. *Eats, Shoots & Leaves: The Zero Tolerance Approach to Punctuation*. London, UK. Profile Books Ltd. Pp 36–37 and pp 39–42.

(For reasons of copyright restrictions we are unable to reprint the extract.)